

Wiegand Repeater Wiegand Converter Dial-Up Modem



WIK REPEATER

Wiegand Repeater

- Wiegand Data Repeater (1 pair)
- WIK Repeater TX, RX
- Connect WIK Repeater (TX) to RF Reader
- Connect WIK Repeater (RX) to Controller
- Power: DC12V/30mA

ITEM	Specification
Input Format	Wiegand
Output Format	Wiegand
Power	DC12V
Operating Environment	0° C ~ 70° C 10 ~ 90% RH(Non-Condensing)
Dimension	65(W)mm x 25(H)mm x 46(D)mm



WIK CONVERTER

Wiegand Converter

- Reader Output Data Converter

ITEM	Specification
Input Format	Wiegand, ABA Track II, RS232
Output Format	Wiegand, ABA Track II, RS232
Power	DC12V/30mA
Operating Environment	0° C ~ 70° C 10 ~ 90% RH(Non-Condensing)
Dimension	55(W)mm x 15(H)mm x 55(D)mm



ROADSTER V.92

Dial-Up Modem

ITEM	Specification
56Kbps (download)	Auto-negotiates V.90 & V.92
48Kbps(upload)	PCM Upstream
Error Correction	ITU-T V.42, MNP 2-4, MNP 10EC
Data Compression	ITU-T V.44, V.42bis, MNP 5
Maximum Throughput	230,400bps
Fax Send/ Receive Speeds	14,000bps (Class 1 & 2)