



IDTECK Co., Ltd.

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



Architect & Engineer Specification

FACE006EX Facial & Proximity Reader

November 14, 2005

1 Introduction

The intent of this document is to describe the specification of FACE006EX facial recognition & proximity reader manufactured by IDTECK Co., Ltd. All the information is provided in detail for system architect and engineers designing access control system.

2 Description

FACE006EX Face & PIN proximity Reader shall provide easy and versatile solution to access control. With facial recognition and built-in 125KHz proximity reader port, it shall dynamically control up to 10,000 users. Combined with iTDC or iCON100 controller, the FACE006EX shall provide easy yet secure access control solution.

3 Mechanical Specification

- 3.1 The FACE006EX biometric reader shall measure 5.1" x 7" x 1.9" (130 x 187 x 54mm). FACE006EX shall arrive disassembled and contains following;
 - 3.1.1 A wall mounting plate
 - 3.1.2 The body that mounts to the wall mounting plate
- 3.2 The FACE006EX shall have a dark pearl gray body
- 3.3 The FACE006EX shall weight 600g (Packaged weight for shipping shall be 700g)

4 Electrical Specification

- 4.1 The FACE006EX shall contain 32bit DSP and 16bit/8bit Microprocessor
- 4.2 The FACE006EX shall contain memory as following.
 - 4.2.1 Face Module shall have following memory
 - 4.2.1.1 Program memory of 32KByte EPROM
 - 4.2.1.2 Data memory of 64MByte Flash memory
 - 4.2.2 Controller part of FACE006EX shall have following memory
 - 4.2.2.1 Program memory of 256Byte Flash.
 - 4.2.2.2 Data memory of 512KByte SRAM.
- 4.3 The FACE006EX shall contain 122 x 32 pixel LCD.
- 4.4 The FACE006EX shall have a 16 key numeric Keypad.
- 4.5 The FACE006EX shall indicate its status through red, green, yellow LEDs and rainbow LED.
- 4.6 The FACE006EX shall have piezo buzzer for the beeper.
- 4.7 The FACE006EX shall contain internal speaker for voice command.
- 4.8 Dual temper switch shall be built in to the FACE006EX to provide safe operation.
- 4.9 The FACE006EX facial recognition reader shall operate on 12V. Max 1A.

5 Face recognition Specification

- 5.1 The FACE006EX shall include built in facial recognition module.
- 5.2 10,000 facial templates shall be stored in dual face templates for accurate recognition.
- 5.3 Dual face template size shall be 240bytes.
- 5.4 The FACE006EX shall include Built-in CCD camera with 230,000 pixels.

6 RFID reader Specification

- 6.1 The FACE006EX shall include built-in 125KHz RF reader port for connecting various RF readers.
- 6.2 Reading Range of FACE006EX shall vary depending on the types of reader and card that are connected.



IDTECK Co., Ltd.

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



7 Communication Specification

- 7.1 FACE006EX shall support 26 bit Wiegand output to the controller.
- 7.2 FACE006EX shall support RFID reader which has 26bit Wiegand output.
- 7.3 The FACE006EX shall provide RS422, RS232 and optional TCP/IP communication.
- 7.4 The FACE006EX shall support baud rate of 4800bps, 9600bps(default), 19200bps, and 38400bps software programmable.
- 7.5 Input and Output as following shall be provided by the FACE006EX.
 - 7.5.1 26bit Wiegand and ABA track II shall be supported by FACE006EX.
 - 7.5.2 The FACE006EX shall have 2 video output (NTSC, PAL) with voice output.

8 Environmental Specification

- 8.1 Operating Temperature
 - 8.1.1 The FACE006EX shall operate temperature between 0 ° C ~ +40°C.
- 8.2 Operating Humidity
 - 8.2.1 The FACE006EX shall operate humidity between 10% ~ 90% RH(Non-condensing)

9 Certification and Approvals

- 9.1 The FACE006EX shall have following certification
 - 9.1.1 FCC certification
 - 9.1.2 UL certification
 - 9.1.3 CE certification
 - 9.1.4 MIC certification

Technical Support Contact Information:

IDTECK

5F, Ace Techno Tower B/D, 684-1 Deungchon-Dong
Gangseo-Gu, Seoul, 157-030
Republic of Korea
Hours: 0900 ~ 1900
Tel: 82-2-2659-0055
Fax: 82-2-2659-0086
E-mail: webmaster@idteck.com
Web: www.idteck.com

Disclaimer

The information in the document has been carefully checked and reliable. IDTECK reserves the right to modify and revise the document without any notice. IDTECK holds no reliability for in accuracies in the document. If you discover any discrepancy in this document please contact us via email listed above or phone.