



IDTECK Co., Ltd.

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



Architect & Engineer Specification

IP20 ASK Format Proximity Card Reader

October 4, 2005

1 Introduction

The intent of this document is to describe the specification of IP20 ASK Format Proximity Card Reader manufactured by IDTECK Co., Ltd. All the information is provided in detail for system architect and engineers designing access control system.

2 Description

The IP20 ASK Format Proximity Card Reader shall provide various applications with one card solution for in and out door use even in harsh environment. The IP20 shall be successfully installed on flat wall mount. Combined with Starwatch Dual or iTDC Pro software, the IP20 shall provide easy yet secure access control solution.

3 Mechanical Specification

- 3.1 The IP20 ASK Format Proximity Card Reader shall measure 1.77" x 4.63" x 0.81" (45 x 117.5 x 20.5mm).
- 3.2 The IP20 shall have a dark pearl gray body.
- 3.3 The IP20 shall weight 180g (Packaged weight for shipping shall be 250g)

4 Electrical Specification

- 4.1 The IP20 ASK Format Proximity Card Reader shall indicate its status through red and green LED and buzzer.
- 4.2 The IP20 shall operate on 12V. Max 150mA.
- 4.3 The IP20 shall have 125KHz frequency.

5 RFID reader Specification

- 5.1 Reading range of the IP20 shall vary depending on the types of the card that are used. The IP20 shall accept following proximity cards with stated reading range.
 - 5.1.1 Passive cards those are stated below shall operate with the IP20 and shall have declared reading range.
 - 5.1.1.1 IPC 80 card (ISO credit card size and thickness) shall have 4inch (10 Cm) reading range.
 - 5.1.1.2 IPC 170 card (clamshell card) shall have 4 inch (10 Cm) reading range.
- 5.2 The IP20 shall have ASK modulation.
- 5.3 The IP20 shall have Reverse power polarity protection

6 Communication Specification

- 6.1 The IP20 shall provide 26bit Wiegand and optional RS232 and ABA Track II magnetic stripe format

7 Environmental Specification

- 7.1 Operating Temperature
 - 7.1.1 The IP20 shall operate temperature between -35 ° C ~ +65 ° C.
- 7.2 Operating Humidity
 - 7.2.1 The IP20 shall operate humidity between 10% ~ 90% RH(Non-condensing)
- 7.3 The IP20 shall be 100% weather proof.



IDTECK Co., Ltd.

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



8 Certification and Approvals

8.1 The IP20 shall have following certification

8.1.1 FCC certification

8.1.2 UL certification

8.1.3 CE certification

8.1.4 MIC certification

Technical Support Contact Information:

IDTECK

5F, Ace Techno Tower B/D, 684-1 Deungchon-Dong

Gangseo-Gu, Seoul, 157-030

Republic of Korea

Hours: 0900 ~ 1900

Tel: 82-2-2659-0055

Fax: 82-2-2659-0086

E-mail: webmaster@idteck.com

Web: www.idteck.com

Disclaimer

The information in the document has been carefully checked and reliable. IDTECK reserves the right to modify and revise the document without any notice. IDTECK holds no reliability for in accuracies in the document.

If you discover any discrepancy in this document please contact us via email listed above or phone.