



**IDTECK Co., Ltd.**

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea  
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



## *Architect & Engineer Specification*

# **SR30RW Smart Card Reader**

*October 4, 2005*

### **1 Introduction**

The intent of this document is to describe the specification of SR30RW Smart Card Reader manufactured by IDTECK Co., Ltd. All the information is provided in detail for system architect and engineers designing access control system.

### **2 Description**

The SR30RW Smart Card Reader shall provide various applications with one card solution for in and out door use even in harsh environment. The SR30RW shall be successfully installed on metal door frame and mullion. Combined with Starwatch Dual or iTDC Pro software, the SR30RW shall provide easy yet secure access control solution.

### **3 Mechanical Specification**

- 3.1 The SR30RW Smart Card Reader shall measure 4" x 5.6" x 0.8".
- 3.2 The SR30RW shall have a dark pearl gray body
- 3.3 The SR30RW shall weight 180g (Packaged weight for shipping shall be 300g)

### **4 Electrical Specification**

- 4.1 The SR30RW shall contain 8bit Microprocessor
- 4.1 The SR30RW Smart Card Reader shall indicate its status through 6 Array LED and buzzer.
- 4.2 The SR30RW shall operate on 12V. Max 180mA.
- 4.3 The SR30RW shall have 13.56MHz frequency.

### **5 RFID reader Specification**

- 5.1 Reading Range of the SR30RW shall be 4"(10cm) using ISO14443 type A Mifare Card(ISC80).

### **6 Communication Specification**

- 6.1 The SR30RW shall provide 26/34bit Wiegand and optional RS232 and ABA Track II magnetic stripe output format
- 6.2 The SR30RW shall have RS232 communication port for Read/Write function.

### **7 Environmental Specification**

- 7.1 Operating Temperature
  - 7.1.1 The SR30RW shall operate temperature between -35 ° C ~ +65 ° C.
- 7.2 Operating Humidity
  - 7.2.1 The SR30RW shall operate humidity between 10% ~ 90% RH(Non-condensing)
- 7.3 The SR30RW shall be 100% weather proof.

### **8 Certification and Approvals**

- 8.1 The SR30RW shall have following certification
  - 8.1.1 FCC certification
  - 8.1.2 UL certification
  - 8.1.3 CE certification
  - 8.1.4 MIC certification



**IDTECK Co., Ltd.**

5F Ace Techno Tower B/D, 684-1, Deungchon-Dong, Gangseo-Gu, Seoul, 157-030, Korea  
Tel : 82-2-2659-0055 Fax : 82-2-2659-0086 www.idteck.com webmaster@idteck.com



---

**Technical Support Contact Information:**

**IDTECK**

5F, Ace Techno Tower B/D, 684-1 Deungchon-Dong  
Gangseo-Gu, Seoul, 157-030

Republic of Korea

Hours: 0900 ~ 1900

Tel: 82-2-2659-0055

Fax: 82-2-2659-0086

E-mail: [webmaster@idteck.com](mailto:webmaster@idteck.com)

Web: [www.idteck.com](http://www.idteck.com)

**Disclaimer**

The information in the document has been carefully checked and reliable. IDTECK reserves the right to modify and revise the document without any notice. IDTECK holds no reliability for in accuracies in the document. If you discover any discrepancy in this document please contact us via email listed above or phone.